

S-Band, GaN/SiC, RF Power Transistor

2.9 - 3.4 GHz | 400W | 60 % Efficiency typ | 13 dB Gain typ | 90 V | 1µs Pulse Length, 1% Duty Cycle

IGN2934S400 and IGN2934S400S are high power GaN-on-SiC RF power transistors that have been designed to suit the unique needs of modern radar systems. They supply a minimum of 400W of peak output power, with an associated 13dB of gain typically and 50% efficiency. They operate from a 90V supply voltage. For optimal thermal efficiency, the transistors are housed in a metal-based package with an epoxy-sealed ceramic lid.



FEATURES

- GaN on SiC HEMT Technology
- Output Power >400W
- Pre-matched Input and Output Impedances
- High Efficiency - 60% typical
- 100% RF Tested under 1µs, 1% duty cycle pulse conditions
- RoHS and REACH Compliant

APPLICATIONS

- S-band Radar Systems




Table 1. RF Electrical Characteristics (Case temperature = 30 °C unless otherwise stated)

Parameter	Symbol	Min	Typ	Max	Units	Test Conditions
Gain	G		13		dB	$P_{OUT} = 400W$ $f = 2.9, 3.15, 3.4 \text{ GHz}$ 1µs pulse length, 1% duty cycle $V_{DS} = 90V, I_{DQ} = 40mA$
Drain Efficiency	η		50		%	
Pulse Droop	D	0		-0.2	dB	
Input Return Loss	IRL	7	12	18	dB	
VSWR Mismatch Stability	VSWR-S	2:1				
VSWR Withstand	VSWR-LMT	5:1				

Note: Consult Integra Technologies Application Note 001 for information on how RF output power and pulse droop are measured.

Table 2. Absolute Maximum Ratings (Not Simultaneous)

Parameter	Symbol	Value	Units	Test Conditions
DC Drain-Source Voltage	V_{DS}	300	V	25 °C
DC Gate-Source Voltage	V_{GS}	-8 to +1	V	25 °C
DC Drain Current	I_D	18	A	25 °C
DC Gate Current	I_G	3.6	mA	25 °C
RF Input Power	$P_{RF,IN}$	90	W	25 °C
Operating Channel Temperature	T_J	-55 to +225	°C	
Storage Temperature	T_{STG}	-55 to +150	°C	
Soldering Temperature	T_{SOLDER}	260 for 60s	°C	

Note: Operation outside the limits given in this table may cause permanent damage to the transistor

Table 3. DC Electrical Characteristics (Case temperature = 25 °C unless otherwise stated)


Parameter	Symbol	Min	Typ	Max	Units	Test Conditions
Gate Pinch-Off Voltage	V_P	-5.0			V	$V_{DS} = 90V, I_{DS} = 1mA$
Quiescent Gate Voltage	V_Q		-4.0		V	$V_{DS} = 90V, I_{DS} = 40mA$

Table 4. Thermal Resistance (Case temperature = 85 °C unless otherwise stated)

Parameter	Symbol	Min	Typ	Max	Units	Test Conditions
Peak Thermal Resistance, Channel to Case	$R_{TH(IC)}$		TBA		°C/W	$P_{diss} = 400W$ 1μs pulse length, 1% duty cycle $V_{DS} = 90V$

Table 5. Matching Circuit Impedances (Case temperature = 25 °C unless otherwise stated)

Frequency (GHz)	Z_{IF}	Z_{OF}	Units	Test Conditions
2.9	4.5 - j 5.7	4.3 - j 3.6	Ω	$P_{OUT} = 400W$ 1μs Pulse length, 1% Duty Cycle $V_{DS} = 90V, I_{DQ} = 40mA$
3.15	4.2 - j 4.4	4.2 - j 2.3	Ω	
3.4	4.1 - j 3.3	4.3 - j 1.2	Ω	



TYPICAL RF PERFORMANCE




Figure 1




Figure 2




Figure 3





Figure 4


TEST FIXTURE




Bill of Materials for IGN2934S400 Test Fixture

Designator	Description	Quantity
C1, C6, C10	CAP 8.2pF, 250V, 0805	3
C2	CAP 15pF, 250V, 0603	1
C3	CAP 1000pF, 100V, 0805	1
C4	CAP 100pF, 250V, 0603	1
C5	CAP 10pF, 250V, 0603	1
C7	CAP 100pF, 250V, 0805	1
C8, C9	CAP 0.1μF, 100V, 0805	2
C11	CAP 10μF, 100V, 2220	1
L1	IND 6.8nH, 0603	1
R1	RES 100Ω, 0603	1
R2, R3	RES 5.11Ω, 0603	2
R5	RES 10Ω, 0805	1
F1	FUSE 10A	1
PC Board Type	ROGERS RO4350B 30mil, 1/1oz. Copper	2

PACKAGE PL44E1



BOLT-DOWN FLANGE OPTION
IGN2934S400



EARLESS FLANGE OPTION
IGN2934S400S

ESD Rating

Parameter	Rating	Standard
ESD Human Body Model (HBM)	TBD	ESDA/JEDEC JS-001-2012
ESD Charged Device Model (CDM)	TBD	JEDEC JESD22-C11F
Moisture Sensitivity Level (MSL)	Unlimited Shelf Life	IPC/JEDEC J-STD-020

RoHS Compliance

Integra Technologies, Inc declares that its GaN and LDMOS Transistor Products comply with EU Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS2), as adopted by EU member states on January 2, 2013 and amended on March 31, 2015 by EU Directive 2015/863/EU.

REACH Compliance

Integra Technologies supports EU Regulation number 1907/2006 concerning the Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) as these apply to Integra semiconductor products, development tools, and shipping packaging.

In support of the REACH regulation, Integra will:

- Inform customers and recipients of Integra product if they contain any substances that are of very high concern (SVHC) per the European Chemical Agency (ECHA) website.
- Notify ECHA if any Integra product that contains any SVHCs which exceed guidelines for REACH chemicals by weight per part number and for total content weight per year for all products produced in or imported to the European market.
- Cease shipments of product containing REACH Annex XIV substances until authorization has been obtained.
- Cease shipment of product containing REACH Annex XVII chemicals when restrictions apply.

Integra has evaluated its materials, BOMs, and product specifications and product and has determined that this transistor conforms to all REACH and SVHC regulations and guidelines. Integra has implemented actions and control programs that will assure continued compliance.

Disclaimer

Integra Technologies Inc. reserves the right to make changes without further notice to any products herein. Integra Technologies Inc. makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Integra Technologies Inc. assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Integra Technologies Inc. products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Integra Technologies Inc. customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Integra Technologies Inc. for any damages resulting from such improper use or sale.

DEFINITIONS:

DATA SHEET STATUS

Advanced Specification - This data sheet contains Advanced specifications.

Preliminary Specification - This data sheet contains specifications based on preliminary measurements and data.

Final Specification - This data sheet contains final product specifications.

MAXIMUM RATINGS Stress above one or more of the maximum ratings may cause permanent damage to the device. These are maximum ratings only operation of the device at these or at any other conditions above those given in the characteristics sections of the specification is not implied. Exposure to maximum values for extended periods of time may affect device reliability.

Integra Technologies, 321 Coral Circle, El Segundo, CA 90245-4620 | Phone: 310-606-0855 | Fax: 310-606-0865